



SE1220C

12V 2.0AH



**Sealed Rechargeable
Lead Acid (VRLA / SMF) Battery**

SPECIFICATIONS

Dimensions and Weight

Length	(mm / inch)	144 / 5.67
Width	(mm / inch)	24 / 0.94
Height	(mm / inch)	65 / 2.56
Total Height	(mm / inch)	65 / 2.56
Weight	(Kg / lbs)	0.6 / 1.32

Performance Characteristics

Nominal Voltage	12V
Number of cell	6
Design Life	3~5 years

Nominal Capacity 25oC

20 hour rate (0.08A, 10.5V)	1.6Ah
10 hour rate (0.15A, 10.5V)	1.5Ah
5 hour rate (0.27A, 10.5V)	1.35Ah
1 hour rate (1.08A, 9.6V)	1.08Ah

Internal Resistance	
Fully Charged battery 25oC	150 Ohms

Self-Discharge	
3% of capacity declined per month at 20oC	

Operating Temperature Range	
Discharge	-20~60oC
Charge	-10~60oC
Storage	-20~60oC

Max. Discharge Current 25oC	24A (5s)
-----------------------------	----------

Short Circuit Current	60A
-----------------------	-----

Charge Methods : Constant Voltage Charge 25oC

Cycle use	14.5-14.9V
Maximum charging current	0.64A
Temperature compensation	-30mV/oC
Standby use	13.6-13.8V
Temperature compensation	-20mV/oC

Manfrs :

SEALED ENERGY SYSTEMS

72, HSIDC Industrial Area, Ambala Cantt- 133006, Haryana, India

Tel : 0171- 2698389, 2699054, 3208757

Fax : 0171- 2698054

E-mail : info@sesbatteries.com