

Sealed Rechargeable Lead Acid (VRLA / SMF) Battery



SPECIFICATIONS

Dimensions and Weight

Length	(mm / inch)	165 / 6.50
Width	(mm / inch)	125 / 4.92
Height	(mm / inch)	175 / 6.89
Total Height	(mm / inch)	182 / 7.17
Weight	(Kg / lbs)	9.75 / 21.5

Performance Characteristics

Nominal Voltage	12V
Number of cell	6
Design Life	3-5 years

Nominal Capacity 77oF(25oC)

20 hour rate (1.4A, 10.5V)	26Ah
10 hour rate (2.65A, 10.5V)	25.5Ah
5 hour rate (4.8A, 10.5V)	23Ah
1 hour rate (19.6A, 9.6V)	19.6Ah

Internal Resistance	
Fully Charged battery 77oF(25oC)	11mOhms

Self-Discharge	
3% of capacity declined per month at 20oC	

Operating Temperature Range	
Discharge	20~60oC
Charge	10~60oC
Storage	20~60oC

Max. Discharge Current 77oF(25oC)	310A(5s)
-----------------------------------	----------

Short Circuit Current	1400A
-----------------------	-------

Charge Methods: Constant Voltage Charge 77oF(25oC)

Cycle use	14.5-14.9V
Maximum charging current	11.2A
Temperature compensation	-30mV/oC
Standby use	13.6-13.8V
Temperature compensation	-20mV/oC

Manfrs :

SEALED ENERGY SYSTEMS

72, HSIDC Industrial Area, Ambala Cantt- 133006, Haryana, India

Tel : 0171- 2698389, 2699054, 3208757

Fax : 0171- 2698054

E-mail : info@sesbatteries.com